



Karta techniczna produktu

Chemmot Ewa Kumorek spółka komandytowa
PL 32-050 Skawina, ul. Józefa Piłsudskiego 59

Telefon: 12 276 75 45
Telefax: 12 276 78 20

DECO COLOR® znak towarowy CHEMMOT®
DECO COLOR® najlepiej postrzegany brand farb i lakierów w aerozolu

Trade name	
PENETRATING OIL by DECO COLOR® aerosol line	
Article No	
30 680	
Seller/Manufacturer	
Chemmot Ewa Kumorek spółka komandytowa; Józefa Piłsudskiego 59, 32-050 Skawina, Polska	
Product's description	
<p>Perfect rust remover and effective grease. Contains molybdenum disulfide (MoS₂) molecules which reduce a friction. Makes to surface more resistant and strong. Due to its special properties used unscrewing even the most rusted screws for unscrewing even the most rusted screws, hinges and bolts. Used also as lubricant for sliding surfaces, maintenance of brake systems and all kinds of chains. This product is applicable for quick repairs during production.</p>	
Main features	
<p>Molybdenum disulfide molecules (MoS₂) Dissolves rust and slacks all rusted parts Anticorrosive properties Penetrating properties Reaches even the smallest capillary hollow of the surface Allows for spot application For indoor and outdoor use CFC free</p>	
Physical and Chemical Properties	
Capacity	400 ml
Application temperature	15-25°C
VOC content	about 85%
Solids content	about 15%
Usage	
<p>Prepare the surface; Clean carefully, degrease, and be sure places you would like to apply to be dry. Shake container vigorously for around 1 minute. Apply selected places evenly from 30 cm. In case of inaccessibility of some places, please use actuator (pipe/tube). Wait few minutes and disconnect corroded, cured or defective elements. If necessary wipe excess with a soft cloth.</p>	
Technical Data Sheet version 05 from 01/03/2022	