



Karta techniczna produktu

Chemmot Ewa Kumorek spółka komandytowa
PL 32-050 Skawina, ul. Józefa Piłsudskiego 59

Telefon: 12 276 75 45
Telefax: 12 276 78 20

DECO COLOR® znak towarowy CHEMMOT®
DECO COLOR® najlepiej postrzegany brand farb i lakierów w aerozolu

Trade name	
SILICON SPRAY by DECO COLOR® aerosol line	
Article No	
30 710	
Seller/Manufacturer	
Chemmot Ewa Kumorek spółka komandytowa; Józefa Piłsudskiego 59, 32-050 Skawina, Polska	
Product's description	
<p>Hydrophobic lubricant for preservation of rubber and plastic parts of the car, home and industry. Protects against water and oxidation. Protects rubber parts against drying and freezing. Preserves plastic and makes it more glossy. Refreshes mat paint coatings. Helps in mounting windows. Good grease for locks, hinges and chains. Helps to remove elements from their forms. Gives electrical insulation due to its ant statistic properties.</p> <p>.</p>	
Main features	
<p>Odourless, non-toxic, colourless Reduces friction, eliminates creaks and squeaks Resistant to temperatures from - 50°C to + 200°C Petrol resistance Weather condition resistance Good insulator Antistatic: does not attract dirt and dust For indoor and outdoor use CFC free</p>	
Physical and Chemical Properties	
Capacity	400 ml
Colour	clear
Gloss	high gloss / mat
Application temperature	15-25°C
High temperature resistance	from -50°C up to 200°C
VOC content	about 70%
Solids content	about 30%



Karta techniczna produktu

Chemmot Ewa Kumorek spółka komandytowa
PL 32-050 Skawina, ul. Józefa Piłsudskiego 59

Telefon: 12 276 75 45
Telefax: 12 276 78 20

DECO COLOR® znak towarowy CHEMMOT®
DECO COLOR® najlepiej postrzegany brand farb i lakierów w aerozolu

Usage

Prepare the surface; Clean carefully, degrease, and be sure places you would like to apply grease to be dry.

Shake container vigorously for around 1 minute.

Apply selected places evenly from 30 cm. In case of inaccessibility of some places, please use actuator (pipe/tube).

Wait few minutes.

If necessary wipe excess with a soft cloth.

Could be used to car's boot seals, doors, hood at winter periods as well as after each car washing.

Technical Data Sheet version 05 from 01/03/2022